

INSUNG ENPLA LED Lighting - Compact LED Long Lamp



Model : INL-CL40C-57K2

Lamp

PHOTO

Features	Type/ Condition	Specification
소비전력	@220V 60Hz	40 W
정격전압		AC 220 V
입력전압범위		AC 200 ~ 240 V
입력전류	@220V 60Hz	AC 0.189A
역률	@220V 60Hz	Min 0.9
SMPS 출력 효율	@220V 60Hz	Min 0.85
광속	@220V 60Hz	6,300 lm
광효율	@220V 60Hz	145 lm/W
연색성	@220V 60Hz	80 Ra
색온도	@220V 60Hz	5700 K
제품중량		810g
베이스 캡		E39/E40
조광기능		None
방사각		360°
크기		Φ 104 x L258mm



※ All of these data is based on Insungenpla Lab's.

General

LED	LG 이노텍
Power ON	Soft Start
수명	40,000 시간이상
동작온도	-20 ~ 45°C

Material

Top Cover	①	Poly Carboante, LB-1010W, Starex
Heat Sink Cap	②	Poly Carboante, LB-1010W, Starex
LED Cover	③	Poly Carboante, SABIC
Heat Sink Frame	④	AL 6063
End Cover	⑤	Poly Carboante, TEJIN, SAMYANG
Power PCB		FR-4 PCB, t1.6
LED Module PCB		FR-4 PCB, t1.0 (End PCB t1.0)

Dimension

