

SPECIFICATIONS (NT-101)

Specifications	NT-101
Rotational Range	+40~150°C
Temperature Difference	10 Over
Temperature Tolerance	off point±5°C
	on point -7°C
Power Rating	AC 125/15A, AC 300V/7.2A, DC 24V/10A
Contact Resistance	50mΩMax
Insulating Resistance	100MΩ at DC 500V
Withstand Voltage	1 minute at AC 1,500V
Withstand Temperating	150°C

SPECIFICATIONS (NT-102)

Specifications	NT-102
Rotational Range	+40~150°C
Temperature Difference	on point -10°C
Temperature Tolerance	off point±5°C
	on point -10°C
Power Rating	AC 125/15A, AC 300V/7.2A, DC 24V/10A
Contact Resistance	70mΩMax
Insulating Resistance	100MΩ at DC 500V
Withstand Voltage	1 minute at AC 1,500V
Withstand Temperating	150°C

SPECIFICATIONS (NT-103)

Specifications	NT-103
Rotational Range	+60~180°C
Temperature Difference	10 Over
Temperature Tolerance	off point±5°C
	on point -7°C
Power Rating	AC 125/15A, AC 300V/7.2A, DC 24V/10A
Contact Resistance	50mΩMax
Insulating Resistance	100MΩ at DC 500V
Withstand Voltage	1 minute at AC 1,500V
Withstand Temperating	180°C